

DECLARATION OF PERFORMANCE

No. **PMB 75/130-60**

1. Name and identity code:

Bitumen for paving ELASTER BM4 PMB 75/130-60 **CE**

2. Name and address of manufacturer:

CEPSA COMERCIAL PETROLEO, S.A. Pº de la Castellana, nº 259 A – Torre CEPSA 28046 Madrid (Spain)

Tel.: 91 337 60 00 www.cepsa.es

3. Applications:

Construction and maintenance of roads, aerodromes and other paved areas

4. System of assessment and verification of performance compliance: 2+

5. Notified body:

AENOR 0099

• Task performed: Factory control assessment

• Certificates: 0099/CPR/B11/0203 – Date issued: 30/07/2010

6. Declared performance:

Essential characteristics	Performance	Harmonised technical specifications
Consistency at intermediate service temperatures		
Penetration at 25° C	Class 7	
Consistency at high service temperatures		
Softening point	Class 6	
Cohesion		
Strength-Ductility (traction at 50 mm/min)	Class 4	
Durability. Resistance to hardening (EN 12607-1)		EN 14023:2010
Retained penetration	Class 7	EN 14023.2010
Increased softening point	Class 3	
Change of mass	Class 5	
Fragility at low service temperatures		
FRAASS fragility point (EN 12593)	Class 7	
Elastic recovery		
Elastic recovery at 25°C	Class 4	



- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

Gerardo Pardo Alvarez-Buylla Director of the Asphalt Unit CEPSA COMERCIAL PETRÓLEO, S.A. Madrid, 30 april 2021