

STATEMENT OF CHARACTERISTICS

No. **C60B5 MBC**

**1. Name and identification code:**

Cationic bituminous emulsion  
EMASFALT MBC  
C60B5 MBC



**2. Name and address of manufacturer:**

CEPSA COMERCIAL PETRÓLEO, S.A.  
Pº de Castellana, nº 259 A – Torre CEPSA  
28046 Madrid (Spain)  
Tel.: + 34 91 337 60 00  
[www.cepsa.es](http://www.cepsa.es)

**3. Expected use:**

Asphalt concrete with dense-graded aggregate

**4. Characteristics performance assessment and verification system: 2+**

**5. Notified body:**

- AENOR 0099
- Task carried out: On-site factory assessment
- Certificates: 0099/CPR/B11/0216 – Issue date: 30/7/2010

**6. Stated characteristics:**

Essential characteristics	Features	Harmonised technical specifications
<b>Emulsion</b>		EN 13808:2013
Creep time (2mm at 40 C)	Class 3	
Effect of water on the bonding agent adhesive properties (adhesion)	Class 3	
Break value	Class 5	
<b>Recovered binder</b>		
<b>Consistency at intermediate service temperatures</b>		
Penetration at 25 C	Class 3	
<b>Consistency at high service temperatures</b>		
Softening point	Class 6	
<b>Stabilized binder (Stage I Durability)</b>		
<b>Consistency at intermediate service temperatures</b>		
Penetration at 25 C	Class 3	
<b>Consistency at high service temperatures</b>		
Softening point	Class 6	

- The characteristics of the product identified in point 1 are in compliance with those declared in point 6.
- This statement of characteristics is issued under the sole responsibility of the manufacturer mentioned in point 2.
- Signed by and in representation of the manufacturer:

A handwritten signature in blue ink, consisting of several overlapping loops and a vertical line extending downwards.

Gerardo Pardo Alvarez-Buylla  
Managing Director of the Asphalt Unit  
CEPSA COMERCIAL PETRÓLEO, S.A

Madrid, 30 april 2021