

STATEMENT OF CHARACTERISTICS

No. C65B2 TRG

1. Name and identification code:

Cationic bituminous emulsion EMASFALT TRG-2 C65B2 TRG

2. Name and address of manufacturer: CEPSA COMERCIAL PETRÓLEO, S.A. Pº de Castellana, nº 259 A – Torre CEPSA 28046 Madrid (Spain) Tel.: + 34 91 337 60 00 www.cepsa.es

3. Expected use: Surface treatment using sprayed gravel

4. Characteristics performance assessment and verification system: 2+

5. Notified body:

- AENOR 0099
- Task carried out: On-site factory assessment
- Certificates: 0099/CPR/B11/0210 Issue date: 30/7/2010 0099/CPR/B11/0211 – Issue date: 30/7/2010 0099/CPR/B11/0212 – Issue date: 30/7/2010 0099/CPR/B11/0215 – Issue date: 30/7/2010 0099/CPR/B11/0216 – Issue date: 30/7/2010

6. Stated characteristics:

Essential characteristics	Features	Harmonised technical specifications
Emulsion		
Creep time (2/4mm at 40°C)	Class 4/5	
Effect of water on the adhesive properties of the bonding agent (adhesion)	Class 3	
Break value	Class 2	
Recovered binder		
Consistency at intermediate service temperatures		
Penetration at 25°C	Classes 4 and 7	EN 13808:2013
Consistency at high service temperatures		
Softening point	Classes 6 and 8	
Stabilized binder (Stage I Durability)		
Consistency at intermediate service temperatures		
Penetration at 25°C	Classes 3 and 5	
Consistency at high service temperatures		
Softening point	Classes 6 and 8	

CE



- The characteristics of the product identified in point 1 are in compliance with those declared in point 6.
- This statement of characteristics is issued under the sole responsibility of the manufacturer mentioned in point 2.
- Signed by and in representation of the manufacturer:

Gerardo Pardo Alvarez-Buylla Managing Director of the Asphalt Unit CEPSA COMERCIAL PETRÓLEO, S.A

Madrid, 30 april 2021