

STATEMENT OF CHARACTERISTICS

No. **C67BPF3 MBA**

1. Name and identification code:

Cationic bituminous emulsion
 STYEMUL MBA
 C67BPF3 MBA



2. Name and address of manufacturer:

CEPSA COMERCIAL PETRÓLEO, S.A.
 Pº de Castellana, nº 259 A – Torre CEPSA
 28046 Madrid (Spain)
 Tel.: + 34 91 337 60 00
www.cepsa.es

3. Expected use:

Open-graded cold mix asphalt

4. Characteristics performance assessment and verification system: 2+

5. Notified body:

- AENOR 0099
- Task carried out: On-site factory assessment
- Certificates: 0099/CPR/B11/0212 – Issue date: 30/7/2010

6. Stated characteristics:

Essential characteristics	Features	Harmonised technical specifications
Emulsion		EN 13808:2013
Creep time (2mm at 40°C)	Class 5	
Effect of water on the adhesive properties of the bonding agent (adhesion)	Class 3	
Break value	Class 3	
Recovered binder		
Consistency at intermediate service temperatures		
Penetration at 15°C	Class 1	
Consistency at high service temperatures		
Softening point	Class 9	
Cohesion		
Vailit pendulum cohesion	Class 6	
Stabilized binder (Stage I Durability)		
Consistency at intermediate service temperatures		
Penetration at 25°C	Class 5	
Consistency at high service temperatures		
Softening point	Class 7	
Cohesion		
Vailit pendulum cohesion	Class 6	

- The characteristics of the product identified in point 1 are in compliance with those declared in point 6.
- This statement of characteristics is issued under the sole responsibility of the manufacturer mentioned in point 2.
- Signed by and in representation of the manufacturer:

A handwritten signature in blue ink, consisting of several overlapping loops and a vertical line extending downwards.

Gerardo Pardo Alvarez-Buylla
Managing Director of the Asphalt Unit
CEPSA COMERCIAL PETRÓLEO, S.A

Madrid, 30 april 2021