

DECLARATION OF PERFORMANCE

JUNTOPLAST C**1. Name and identity code**

Juntoplast C

N1 type thermal sealing mastic



0099

2. Name and address of manufacturer:

CEPSA COMERCIAL PETROLEO, S.A.
Pº de la Castellana, nº 259 A – Torre CEPSA
28046 Madrid (Spain)
Tel.: 91 337 60 00
www.cepsa.es

3. Applications:

Hot-applied product for sealing cracks in roads, airports, bridge decks, car park floors, etc.

4. System of assessment and verification of performance compliance: 4**5. Declared performance: Type N1**

Essential characteristics	Performance	Harmonised technical specifications
Cone penetration at 25°C, 5s, 150g, in 0.1 mm	40-130	EN 14188-1:2005
Softening point in °C	>85	
Density at 25°C in mg/m ³	>1.1	
Penetration and recovery (resilience) in %	>60	
Creep in mm	<2	
Stability to heat (168h at 70°C)		
Cone penetration at 25°C, 5s, 150g, in 0.1 mm	40-130	
Penetration and recovery (resilience) in %	>60	



Gerardo Pardo Alvarez-Buylla
Director of the Asphalt Unit
CEPSA COMERCIAL PETRÓLEO, S.A.

Madrid, October 1, 2021