

DECLARATION OF PERFORMANCE

No. **PMB 45/80-75**

**1. Name and identity code:**

Bitumen for paving  
ELASTER RAF BT additive  
PMB 45/80-75



**2. Name and address of manufacturer:**

CEPSA COMERCIAL PETROLEO, S.A.  
Pº de la Castellana, nº 259 A – Torre CEPSA  
28046 Madrid (Spain)  
Tel.: 91 337 60 00  
[www.cepsa.es](http://www.cepsa.es)

**3. Applications:**

Construction and maintenance of roads, aerodromes and other paved areas (sealed against penetration)

**4. System of assessment and verification of performance compliance: 2+**

**5. Notified body:**

- AENOR 0099
- Task performed: Factory control assessment
- Certificates: 0099/CPR/B11/0203 – Date issued: 30/07/2010

**6. Declared performance:**

Essential characteristics	Performance	Harmonised technical specifications
<b>Consistency at intermediate service temperatures</b>		EN 14023:2010
Penetration at 25° C	Class 4	
<b>Consistency at high service temperatures</b>		
Softening point	Class 3	
<b>Cohesion</b>		
Strength-Ductility (traction at 50 mm/min)	Class 2	
<b>Durability. Resistance to hardening (EN 12607-1)</b>		
Retained penetration	Class 7	
Increased softening point	Class 3	
Change of mass	Class 5	
<b>Fragility at low service temperatures</b>		
FRAASS fragility point (EN 12593)	Class 7	
<b>Elastic recovery</b>		
Elastic recovery at 25°C	Class 2	

- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

A handwritten signature in blue ink, consisting of several overlapping loops and a vertical line extending downwards.

Gerardo Pardo Alvarez-Buylla  
Director of the Asphalt Unit  
CEPSA COMERCIAL PETRÓLEO, S.A.

Madrid, May 7, 2024