

STATEMENT OF CHARACTERISTICS

No. **C60BP3 ADH**

**1. Name and identification code:**

Cationic bituminous emulsion  
LASTIREM CR1  
C60BP3 ADH



**2. Name and address of manufacturer:**

CEPSA COMERCIAL PETRÓLEO, S.A.  
Pº de la Castellana, nº 259 A – Torre CEPSA  
28046 Madrid (España)  
Tel.: 91 337 60 00  
[www.cepsa.es](http://www.cepsa.es)

**3. Expected use:**

Tack coat asphalt

**4. Characteristics performance assessment and verification system: 2+**

**5. Notified body:**

- AENOR 0099
- Task carried out: On-site factory assessment
- Certificates: 0099/CPR/B11/0212 – Issue date: 30/7/2010  
0099/CPR/B11/0215 – Issue date: 30/7/2010

**6. Stated characteristics:**

Essential characteristics	Features	Harmonised technical specifications
<b>Emulsion</b>		EN 13808:2013
Creep time (2mm at 40°C)	Class 3	
Effect of water on the adhesive properties of the bonding agent (adhesion)	Class 3	
Break value	Class 3	
<b>Recovered binder</b>		
<b>Consistency at intermediate service temperatures</b>		
Penetration at 25°C	Class 7	
<b>Consistency at high service temperatures</b>		
Softening point	Class 8	
<b>Cohesion</b>		
Vialit pendulum cohesion	Class 6	
<b>Stabilized binder (Stage I Durability)</b>		
<b>Consistency at intermediate service temperatures</b>		
Penetration at 25°C	Class 5	
<b>Consistency at high service temperatures</b>		
Softening point	Class 6	
<b>Cohesion</b>		
Vialit pendulum cohesion	Class 6	

- The characteristics of the product identified in point 1 are in compliance with those declared in point 6.
- This statement of characteristics is issued under the sole responsibility of the manufacturer mentioned in point 2.
- Signed by and in representation of the manufacturer:

A handwritten signature in blue ink, appearing to be "Gerardo Pardo Alvarez-Buylla".

Gerardo Pardo Alvarez-Buylla  
Managing Director of the Asphalt Unit  
CEPSA COMERCIAL PETRÓLEO, S.A

Madrid, 30 april 2021