TRANSMISSIONS



MOTOR VEHICLE LUBRICANTS CEPSA AURIGA TA-40



DESCRIPTION

Oil formulated with highly refined paraffinic base oils and additives that guarantee excellent properties in its specific application.

PRODUCT APPLICATIONS

• CEPSA AURIGA TA-40 oil is specially formulated for use in torque converters and hydraulic transmissions requiring a fluid of this kind.

PRODUCT PERFORMANCE

- High level of anti-friction protection.
- Great oxidation resistance.
- Excellent compatibility with seals and gaskets.
- Long service life.
- Excellent protection of all vital parts of torque converters.

SPECIFICATIONS

SAE 10W

ALLISON C3

CATERPILLAR TO-2

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA AURIGA TA-40
Grado SAE			10W
Density at 15°C	Kg/l	D-4052	0,8831
Flash Point (COC)	°C	D-92	205
Pour Point	°C	D-97	-30
Viscosity at 100°C	cSt	D-445	6,2
Viscosity at 40°C	cSt	D-445	39,1
Viscosity Index		D-2270	100

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.