

## LUBRICANTS FOR INDUSTRIAL USE

# CEPSA COMPRESORES LPG 9

### DESCRIPTION

A synthetic lubricant based on polyalkylene glycol.

#### PRODUCT APPLICATIONS

- Specially designed for the lubrication of gas compressors in which gears and bearings operate under an atmosphere of some gases such as: butane, propane, methane, ethylene, ammonia and vinyl chloride etc.

#### PRODUCT PERFORMANCE

- High antiwear level which increases equipment life.
- Low solubility in gases multiplying its useful service life.
- High detergent/dispersant characteristics. Guarantees equipment cleanliness.
- Excellent viscosity/temperature behaviour. Perfect lubrication at any temperature.

### SPECIFICATIONS

- SULZER BURCKHARDT A.G. K-type compressors
- LINDE A.G.

### TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA COMPRESORES LPG 9
Density at 15°C	kg/l	ASTM D-4052	1,050
Fash Point, COC	°C	ASTM D-92	258
Pour Point	°C	ASTM D-5950	-40
Viscosity at 40°C	cSt	ASTM D-445	189
Viscosity at 100°C	cSt	ASTM D-445	36
Viscosity Index	-	ASTM D-2270	238
Steel Corrosion Test (24h)	-	ASTM D-665A	Pass

### HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.