

### DESCRIPTION ECO-FRIENDLY PRODUCT

High-quality, 100% synthetic oil developed to meet the requirements of the new automatic transmissions used in all types of hybrid and traditional combustion vehicles. The technology used in this product provides optimum protection against wear and guarantees compatibility with electrical circuits.

#### PRODUCT APPLICATIONS

- Formulated to meet the requirements of automatic transmissions used in both plug-in and conventional hybrid vehicles.
- Valid for light vehicles requiring an automatic transmission fluid with low viscosity and in compliance with GM Dexron VI and Ford Mercon LV.

#### PRODUCT PERFORMANCE

- Low viscosity to minimize friction and increase energy efficiency.
- Exceptional cleanliness of the transmission system.
- Protection against wear caused by friction in the transmission.
- Good anti-foaming and dispersant properties.

### SPECIFICATIONS

GM Dexron VI & ULV	Toyota WS JWS 3324	MB 236.15/ 236.17
Nissan Matic S	Ford Mercon LV & ULV	Nissan SP4-M1

### ADDITIONAL QUALITY LEVELS

OEM / ATF	Application
Allison	C4
BMW	ATF 3+ • ATF4; ATF6 • ETL-7045 • ETL-7045 E • ETL-8072B • LA 2634 • LT 71141: M-L12108 • P/N 81 22 9 400 272/275 • P/N 81 22 9 407 858/859 • P/N 83 22 0 024 249 • P/N 83 22 0 024 359 • P/N 83 22 0 026 922 • P/N 83 22 0 142 516 • P/N 83 22 0 397 114 • P/N 83 22 0 402 413 • P/N 83 22 0 403 248/249 • P/N 83 22 2 152 426 • P/N 83 22 2 163 514 • P/N 83 22 2 220 438/440 • P/N 83 22 2 220 442 • P/N 83 22 2 289 720 • P/N 83 22 2 305 396 • P/N 83 22 2 305 397 • P/N 83 22 2 355 599 • P/N 83 22 2 355 601 • P/N 83 22 7 542 290 • P/N 83 22 9 407 765 • P/N 83 22 9 407 807
Citroen	Z 000169756
Daihatsu	D3-SP
Fiat Chrysler Automotives	FCA 8 & 9 Speed ATF • P/N 68218925AA/AB • ASRC • ATF+ • ATF+2 • ATF+3 • ATF+4 AW-1, P/N 68092912AA • Dex-VI, P/N 68043742AA • MB 236.10/12, P/N 05127382AA • P/N 05127382 • P/N 68157995AA/AB • P/N 68333587AA • SP-4, P/N 68171866AA • SP-III • SP-IV, P/N 68171866AA • SP-IV, P/N 68171869AA • Type 7176E • Type 9602
FORD	ESP-M2C138-CJ • ESP-M2C166-H • P/N XT-10-QLV [LV] • P/N XT-12-ULV [ULV] • P/N XT-2-QDX [M] • P/N XT-2-QSM [Syn] • P/N XT-5-QM [V] • P/N XT-6-QSP [SP] • P/N XT-8-QAW [Premium] • P/N XT-9- QMM5 [FRN5] • Spec WSS-M2C922-A1
GM	GM ATF Z1 Saturn P/N 22717466 • AW-1 P/N 19256039 • Dex [GM 6032M] • Dex HP [GMW 16974] • Dex ULV, P/N 19352619v • Dex-B [GM 6032M] • Dex-IIC [6137M] • Dex-IID [GM 6137M] • Dex-IIE [GM 6137M] • Dex-IIIF [GM 6297M] • Dex-IIIG [GM 6417M] • Dex-IIIH [GM N10055] • Dex-VI [GMW 16444] • P/N 19 40 700 • P/N 19 40 767 • P/N 21005966 • P/N 88900925 • P/N 9985010 • P/N 9986195 • Saturn T-IV Fluid, Saturn P/N 22689186 • Type A Suffix A • WS, P/N 88863400 / 88863401

HONDA/ACURA	ATF DW-1 P/N 08200-9008 • ATF Type 3.0 P/N 08200-9016-A • ATF Type 3.1 P/N 08200-9017 • ATF Z1, P/N 08200-9001 • ATF Z1, P/N 08200-9001A
<b>OEM / ATF</b>	<b>Application</b>
HYUNDAI/KIA	ATF RED-1K H S S S • ATF SP-IV L S S N • Genuine ATF H S S S • JWS 3314 H S S S • P/N 00232-19023 H S S S • P/N 040000C90SG L S S N • P/N 04500-00140 H S S S • /N UM040 CH20 Red-1 H S • SP H S S S • SP4-M1 L S S N • SPH-IV L S S N • SP-II H S S S • SP-III H S S S • SP-IV L S S N • SP-IV-RR L S S N • WS, spec NWS-9638
ISUZU	PN 08200-9001 • SCS
JAGUAR	J 02JDE 26444 • JLM 20238 • JLM 20292 • JLM 21044 • K17, Jatco 3100 PL085 • LT 71141 • WSS-M2C922-A1
JAMA	JASO M315 Class 1-A • JASO M315 Class 1-A-LV
LAND ROVER	ATF N402 • AW-1 P/N LR0022460: LV • JWS3309US • P/N TYK500050 • LR023288/023289
MAN	339A • 339D • 339F
MAZDA	ATF M-5 P/N 0000-23-ATF -M5 • ATF N-1 • ATF S-1 • F -1 • JWS3317 • M3 • Type T-IV, JWS 3309 ATF
Mercedes Benz	236.1 • 236.10 • 236.11 • 236.12 • 236.14 • 236.15 • 236.2 • 236.41 • 236.5
Mini	ATF JWS 3309 • P/N 83 22 0 402 413
Mitsubishi	ATF-J2 • ATF-J3 • Dia Queen ATF-MA1 P/N MZ320775 • Dia Queen ATF-PA, P/N 4030401 • Dia Queen AW • DII/DIII • SP, P/N MS991156 • SP-II • SP-III • SP-IV
Nissan	Matic D • Matic J, P/N 999MP-MTJ00P • Matic K • Matic P, P/N 999MP-MTP10P • Matic S, P/N 999MP-MTS00P • Matic W • N402
Peugeot	Peugeot P/N Z 000169756
Porsche	PWS 3309, P/N 000 043 205 28 • LT 71141 • P/N 000 043 204 63 • P/N 000 043 304 00 • P/N 999 917 547 00 (A2), P/N 000 043 205 09
PSA	PSA AL4 / 4HP20 P/N 9730AE • B71 2340
Renault	DP-0 • Matic D2 • SATF-D
Rolls Royce	31493PA
Saab	ATF HP • JWS 3309 • P/N 93 160 393 • P/N 93 165 147
Saturn	Dex-III G • T-IV Fluid, P/N 22689186
Ssangyong	DSIH 5M-52 • DSIH 5M-66
Subaru	ATF HP • P/N K0140Y0700 • P/N SOA635040 • ATF-WS
Suzuki	ATF 2326 • ATF 2384K • ATF 3314 • ATF 3317 • ATF 5D06 • Matic D • Matic J • Matic S
Toyota	JWS 3309, Type T-IV, P/N 08886-81015 • JWS 3324, ATF WS (or NWS9638) • Type D-II • Type T • Type T-II • Type T-III
VOLVO	P/N 1161521 • P/N 1161640 • P/N 1161540 • P/N 31 256 774, 31 256 775
VW/Audi	LT 71141 • G 052 162 (-A1, -A2) [AG4] • G 052 533 • G 052 990 A2 • G 053 001 A2 • G 055 005 A2 • G 055 025 (-A2) • G 055 162 A2 or A6 • G 055 540 A2 • G 060 162 A2 • G 060 540 A2 • G US 000 162

## TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA XTAR MAX HYBRID ATF LV-S
Density at 15°C	Kg/l	D-4052	0.8476
Flash point COC	°C	D-92	>200
Pour point	°C	D-97	-54
Viscosity at 100°C	cSt	D-445	5.996
Viscosity at 40°C	cSt	D-445	29.51
Viscosity Index	-	D-2270	155
Brookfield viscosity -40°C	cP	D-2983	9957

## HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.